
# **SUBMITTAL**

### Manual Radiator | Features:




The American Steam Control manual hand valves are combination shut off and union valves for steam and hot water applications.

These valves can also be converted to thermostatic radiator valves at a later date by simply adding a thermostatic control.

With use of the American Steam Control Unichanger, the system does not have to be drained to change valve cartridges.

## STRAIGHT PATTERN VALVE - DIMENSIONS



## **Specifications**

Application Range:

250° F Max. Temperature: 150 psig Max. Water Pressure: Max. Steam Pressure:

### **Materials:**

Valve Body:

Brass, Nickel Plated

Seat:

Brass

Trim:

**CARTRIDGE 40** 

Casing:

**Brass EPDM** 

15 psig

Disc:

Stainless Steel

Stem:

EPDM (Nordel)

O-Ring Seal:

Hand Wheel:

**High Impact Resistant** 

Plastic

\*Solder end valves are furnished with a MNPT by solder adapter on Inlet side\*

Other Available Body Styles		
Vertical Angle Valve	Horizontal Angle Valve	Straight Valve, Double Union

CUSTOMER	
PROJECT	
ENGINEER	
ARCHITECT	
PRO/PO#	
	5/10 JM

## American Steam Control

Division of Walsh Controls, Inc.

www.americansteamcontrol.com

101 Pennsylvania Blvd Pittsburgh, PA 15228

412-561-2195 1-888-703-3999

Fax: 412-344-8306