Division of Walsh Controls, Inc.

SUBMITTAL


Manual Radiator | Features: Hand/Preset Valves **4+** 5/16" →

The American Steam Control manual hand valves are combination shut off and union valves for steam and hot water applications.

These valves can also be converted to thermostatic radiator valves at a later date by simply adding a thermostatic control.

With use of the American Steam Control Unichanger, the system does not have to be drained to change valve cartridges.

HORIZONTAL ANGLE VALVE - DIMENSIONS



Specifications

Application Range:

Max. Temperature: 250° F Max. Water Pressure: 150 psig Max. Steam Pressure: 15 psig

Materials:

Valve Body: Brass, Nickel Plated

Seat: Brass

Trim: CARTRIDGE 40

Casing: Brass Disc: **EPDM** Stem: Stainless Steel O-Ring Seal: EPDM (Nordel) Hand Wheel: High Impact Resistant

Plastic

Solder end valves are furnished with a MNPT by solder adapter on Inlet side

Other Available Body Styles			
Vertical Angle Valve	Straight Pattern Valve	Straight Valve, Double Union	

CUSTOMER	American Steam Control	
PROJECT	Division of Walsh Controls, Inc.	
ENGINEER	www.americansteamcontrol.com	
ARCHITECT	98 Vanadium Rd., Building D Bridgeville, PA 15017	
PRO/PO#	412-220-9204 1-888-703-3999	
10/16kw	Fax: 412-220-9351	